

## USB 2.0 Hub 4 and 7 Ports



### Features

- 4/7 USB ports up to 100 mA per port or up to 500 mA (with power adapter)
- Supports over current protection
- Supports high-speed (480 Mbps), full-speed (12Mbps) and low-speed (1.5 Mbps) transfer rate
- Plug & Play
- Chains up to 127 USB devices
- USB and ACPI compliant

### System Requirements

- IBM Compatible PC or Mac PC
- USB Host card or USB Hub device
- Windows 98SE / ME / 2000 / XP or MacOS 9.0

### Package Contents

- One USB 2.0 Hub 4 Port or 7 Port
- One USB cable 1.5m
- One power adapter

Specification	USB 2.0 Hub 4 Port	USB 2.0 Hub 7 Port
Interface standard	USB V2.0	USB V2.0
Connectors	4x USB type A female 1x USB type B female, 1x DC male	7x USB type A female 1x USB type B female 1x DC male
Data transfer rate	480 Mbps, 12 Mbps, 1,5 Mbps	480 Mbps, 12 Mbps, 1,5 Mbps
LEDs	1x Power (on/off) 4x Port status	1x Power (on/off) 7x Port status
Power mode	Bus Power/Self Power Mode	Bus Power/Self Power Mode
Cable	USB cable A>B M/M 1.5m	USB cable A>B M/M 1.5m
Enclosure	Plastic	Plastic
EMI	CE & FCC	CE & FCC
Operating temperature	5° - 40° C	5° - 40° C
Storage temperature	-20° - 40° C	-20° - 40° C
Relative humidity	0 - 80% , non condensing	0 - 80% , non condensing