



4x2 HDMI Matrix Switch

33271903

Save time and hassle by automatically switching between your HDMI audio/video sources, using Equip 2X4 HDMI Matrix Switcher. This easy-to-use HDMI Matrix switch ensures seamless transition while switching video and display sources, with EDID copy maintaining your video resolution.

| Specification

HDMI STANDARD	HDMI support 4K*2K input and 3D
HDMI resolution	24/50/60fs/1080p/1080i/720p/576p/576i/480p/480i
Support video color format	24bit/deep color 30bit,36bit, 48bit
Support audio format	DTS-HD/Dolby-trueHD/LPCM7.1/DTS/Dolby-AC3/DSD
Audio output	SPDIF and 3.5mm Stereo
Max transmission bandwidth	340MHz
Max baud rate	10.2Gbps
Input/Output TMDS signal	0.5~1.5Volts p-p
Input/Output DDC signal	5Volts p-p (TTL)
Input cable distance.	≤15m AWG24 HDMI standard cable
Output cable distance	≤25m AWG24 HDMI standard cable
Max working current	1300mA
Power adapter format	Input:AC (50HZ, 60HZ) 100V-240V; Output: DC5V/2A
Operating Temperature range	(-15 to +55°C)
Operating Humidity range	5 to 90%RH (No Condensation)



www.equip-info.net

| Ordering Information

PN	EAN	Package Size	Weight
33271903	4015867197486	250X27X75mm	380g

| Package Contents

- 5V power adapter x 1
- Remote x 1
- User manual x 1

