

www.equip-info.net



Catalog 2010

Streamline your access to all the gadgets at home, in the office, and on the go.





Universal Series

To Spread and Distribute

- USB Hub
- USB HDD Enclosure
- USB Docking
- USB Card Reader
- Charger/ Power Strip
- USB Converter/Extender



USB 3.0 4-Port Hub

- compliant to USB 3.0/2.0/1.1 specifications
- USB bus-powered or self-powered
- hot swappable, no driver required
- one up-stream port and four down-stream ports
- business card size, 42g weight
- supports WIN XP/Vista/7, Mac OS V8.6 or Above
- incl. 5V/4A power adapter

128945



USB2.0 4-Port Mini Hub

- compliant to USB 2.0/1.1
- data transfer rate up to 480Mbps
- Plug & Play
- over-current protection
- self-powered
- dust protection cap
- supports WIN2000/XP/Vista/7, Mac OS V9.2 or Above

128583



USB 2.0 Travel Hub

- one up-stream port and four down-stream ports
- over-voltage protection
- USB bus-powered or self-powered
- supports WIN98SE/ME/2000/XP/Vista/7, Mac OS V9.0 or Above
- incl. power adapter
- incl. USB 2.0 A -> B M/M connection cable, 1m

128944



USB 3.0 4-Port Stand Hub

- data transfer rate up to 5Gbps (Super speed)
- backwards compatible with USB 2.0/1.1
- USB bus-powered or self-powered
- Plug & Play, hot swappable
- LED indicators for Link/AC power and device connection
- supports WIN XP/Vista/7, Mac OS V8.6 or Above
- incl. 5V/3A power adapter

128946



USB 2.0 Cable Hub 3+1-Port

- compatible with USB 2.0 specification
- data transfer rate up to 480Mbps
- connectors: 3 x USB type A female, 1 x mini 5-pin USB type B male
- over-current and over-voltage protection
- Plug & Play
- supports WIN98SE/ME/2000/XP/Vista/7, Mac OS V9.2 or above

128547



USB 2.0 Hub 7-Port

- one up-stream port and seven down-stream ports
- over-voltage protection
- USB bus-powered or self-powered
- supports WIN98SE/ME/2000/XP/Vista/7, Mac OS V9.22 or above
- incl. 5V/3A power adapter
- incl. USB 2.0 A -> B M/M connection cable

128928



USB 3.0 SATA 3.5" HDD Enclosure

- supports 3.5" SATA / SATA II hard drive
- compliant to USB 3.0/2.0/1.1 Specification
- data transfer rate up to 5Gbps (Super speed)
- supports USB Mass Storage Class, Bulk-Only Transport Specification Revision 1.3
- compliant with Serial ATA Specification Revision 2.6
- supports WIN XP/Vista/7
- incl. 12V/2A power adapter

136635



USB 3.0 SATA 2.5"/3.5" HDD Docking Station

- supports 2.5" or 3.5" SATA hard drives
- compliant with USB 3.0/2.0/1.1 Specifications
- data transfer rate up to 5 Gbps (Super speed)
- supports USB Mass Storage Class, Bulk-Only Transport Specification Revision 1.3
- compliant with Serial ATA Specification Revision 2.6
- incl. 12V/2A power adapter
- supports WIN XP/Vista/7

128579



eSATA/USB 2.0 Docking Station

- supports 2.5" or 3.5" SATA hard drives
- compliant with USB 2.0/1.1 Specifications
- SATA transfer rate up to 3.0Gbps
- dual interface: eSATA and USB
- Plug & Play
- dust protection cap
- LED indicators for power and access
- incl. 12V/2A power adapter
- supports WIN98/2000/XP/Vista/7, Mac OS V8.6 or Above

128574



USB 3.0 SATA 2.5" HDD Enclosure

- supports 2.5" SATA / SATA II hard drive
- compliant to USB 3.0/2.0/1.1 Specification
- data transfer rate up to 5Gbps (Super speed)
- Supports USB Mass Storage Class, Bulk-Only Transport Specification Revision 1.3
- compliant with Serial ATA Specification Revision 2.6
- supports WIN XP/Vista/7

136625



USB 2.0 Docking Station

- supports Hot Plug and Play functions
- supports USB High-Speed and Full-Speed Operation
- 53 in 1 card reader
- 4 x port USB Hub
- 1 x 10/100 Ethernet LAN port
- 2 channel audio (Mic/Spk)
- 1 x PS/2 interface (keyboard, mouse)
- 1 x Serial port (DB9-pin male)
- 1 x e-SATA port
- incl. docking stand
- incl. USB cable 1.2m
- incl. setup CD
- incl. power supply

128575



USB 2.0 Card Reader Internal 3.5" + USB Port

- supports SM/xD, SD/MMC, MS and CF/MD memory slots
- allows direct data transfer between different types of memory cards
- mini size, suitable for all desktop PC enclosure
- USB 2.0 high-speed data transfer rate up to 480Mbps
- two LED indicators for in-use status
- 1x USB 2.0 downstream port for convenient access
- incl. beige, black and silver color bezel for swapping
- supports WIN98/2000/XP/Vista/7, Mac OS V9.2 or Above

128578



USB 2.0 Card Reader 6 in 1

- compliant to USB2.0/1.1 standards
- supports SD, SDHC, MMC, MS, MS Pro, and xD memory cards
- compatible to Mini SD, RS MMC, MS Duo, MS Pro Duo, and Micro SD/T-Flash (adapter required)
- hot swappable, Plug & Play
- supports WIN98/2000/XP/Vista/7, Mac OS V10.4 or Above

128505



Triple Socket with USB Car Charger

- expands 1 lighter socket to 3
- provides 1 additional USB charging port
- output per socket: DC12V/24V, Max: 2.5A
- output of USB port: DC5V, rating: 500mA
- built-in safety fuse
- On/Off switch
- LED indicator

133342



2-Port USB Travel Charger

- rating: 100-240V 50/60Hz
- output power: 5V/1A
- over-current protection
- LED indicator
- built-in fuse
- weight: 40g

133343



USB 2.0 All-in-One Card Reader

- five memory slots: CF/MD, SD/mini SD/ MMC/RS-MMC, MS/MS-Duo, Micro-SD/ M2
- supports slot to slot read/write operation
- supports WIN98/2000/XP/Vista/7, Mac OS V10.4 or Above

128552



2-in-1 USB 2.0 Car Charger

- compatible with iPhone, iPod and USB devices
- charging indicator LED
- built-in safety fuse
- provides 1 USB slot for most USB charging devices, output 5V/1A

133341



Power Strip

- rating: 220-240V 50/60Hz
- cord length: 1100mm
- compliant with European Standard EN 60884-1: 2002

333280 3-Socket Power Strip

333281 4-Socket Power Strip



USB 2.0 Data Link cable

- compliant with USB 2.0/1.1 Specifications
- 2 x USB A plug, length: 1.1m
- data transfer rate up to 480Mbps
- USB bus-powered
- LED indicator for link
- Plug & Play
- supports WIN98/2000/XP/Vista/7

133338



USB 2.0 Signal Booster

- 5m signal booster via USB 2.0 cable A -> A M/F, 5m
- up to 3 signal booster can be chained
- supports WIN98/2000/XP/Vista/7

133336



7.1-CH Audio Adapter

- USB specification 2.0 compliant
- supports 7.1 Channel for windows, Mac up to 5.1 Channel (Software Included)
- connector: 2 x 3.5mm phone jack (Mic., Headphone)
- supports WIN98/2000/XP/Vista/7, Mac OS V9.0 or above

133345



USB 2.0 active extension cable

- compliant with USB 2.0/1.1 Specifications
- USB 2.0 Type A Male to Type A Female
- over current detection and protection
- USB bus-powered
- LED indicator
- hot swappable, Plug & Play
- supports WIN98/2000/XP/Vista/7, Mac OS V9.0 or Above

133310 10M

133311 15M



USB Extender

- provides a cost effective connection between USB devices and PC via Cat.5e network cable, length up to 45m
- Plug & Play, no software and driver needed
- supports WIN98/2000/XP/Vista/7, Mac OS V9.0 or above

133344



Wireless Notebook Presenter 4-in-1

- PowerPoint presentation control
- 360° wireless mouse function
- multimedia remote control
- laser pointer: 40m
- frequency area: 2400-2483Mhz
- remote range up to 30m indoors and 100m outdoors
- Plug & Play
- incl. USB receiver stick
- supports Win98SE/ME/2000/XP/Vista/7, Mac OS 9.1 or Above

610023



USB 2.0 to SATA & IDE Adapter

- connects IDE and SATA devices simultaneously through a USB port
- works well with 2.5"/3.5" SATA and 2.5"/3.5"/5.25" IDE storage devices
- compliant with USB1.1/USB2.0 specifications
- supports USB mass storage, hot swappable
- safety on/off power switch
- LED indicators for power and data link
- incl. 12V/2A power adapter

133359



USB 1.1 Converter Centronics

- USB A/M -> CN36/M
- USB to IEEE 1284 parallel printer/scanner
- supports WIN98/2000/ME/XP/Vista/7
- incl. setup CD

133313

USB 1.1 Converter Keyboard / Mouse

- USB A Male -> 2 x PS/2 Female
- supports WIN98/2000/ME/XP/Vista/7, Mac OS V8.6 or above
- incl. setup CD

133326



USB 2.0 Share Switch

- compliant to USB 2.0/1.1 standards
- supports EHCI, UHCI and OHCI
- USB bus-powered
- push button and Hot Key (PC only)
- supports WIN98/2000/XP/Vista/7, Mac OS V10.x or above

2-Port 128542

4-Port 128544

Coming soon



Dock to USB cable/to composite AV cable

Dock to USB cable

- dock connector to USB Type A Male
- synchronize music/data between your iPod/iPhone and PC/MAC through this data cable
- hot sync and charge the iPod/iPhone simultaneously
- also works with 133341/133342 car charger and 133343 travel charger

Dock to composite AV cable

- dock connector to RCA connector + USB Type A Male
- play files in iPod/iPhone on TV or home theater display
- USB connection for data sync and charging

134100 Dock to USB cable

134101 Dock to composite AV cable



Mouse Pad

245007/245008/245009

- 230 x 190mm
- 3mm thickness
- jersey cloth surface
- rubber sponge material

245010

- 375 x 250mm, extra-wide coverage allows the vast range of movements
- 3mm thickness
- natural rubber material, anti-slippery

Coming soon



USB 3.0 to SATA Adapter

- compliant to USB 3.0/2.0/1.1 standards
- data transfer rate up to 5Gbps
- supports SATA I/II and IDE devices
- support bisynchronous mode; works with SATA and IDE device simultaneously
- hot swappable, Plug & Play
- supports WIN XP/Vista/7, Mac OS V10.x or above

133369



Expansion Series

To Expand and Grow

- Express Card
- PCI, PCI Express
- SATA, eSATA Adapter, Converter, Front Panel



USB 3.0 Express Card 2-Port

- supports Low-speed (1.5Mbps) / Full-speed (12Mbps) / High-speed (480Mbps) / Super-speed (5Gbps) data rate
- supports USB legacy function
- supports Express Card™ Standard rev. 1.0
- supports WINXP/Vista/7

111832



USB 2.0 Express Card 2-Port

- adding 2x USB 2.0 ports to the Notebook/PC
- USB 2.0 high speed specification up to 480 Mbps
- Express Card/34 Form Factor Module
- USB standard driver supported by Windows and Mac OS
- incl. user manual

111827



RS-232 Serial Express Card 1-Port

- fully compliant with Express Card specification 1.0
- Express Card/34 Form Factor Module
- provides 1x DB9 RS-232 Serial Port
- supports transmission rate up to 230 Kbps
- supports WIN2000/XP/Vista/7
- incl. setup CD and user manual

111829



eSATA II Express Card/34 - 2 Port

- expands the notebook by two additional eSATA II ports
- compliant with Express Specification 1.0a
- two self-contained channels
- SATA II Specification, data transfer rate up to 3.0Gbps
- Express Card data transfer rate up to 250 Mbps
- supports SATA Port-multiplier
- supports WIN2000/XP/Vista/7, Mac OS 10.4 or above
- supports Legacy Command Queuing (LCQ) and Native Command Queuing (NCQ)
- incl. setup-CD and user manual

111818



eSATA/-USB 2.0 Express Card 2-Port

- connects 1x eSATA and 1x USB 2.0 Device to the Notebook/Netbook computer
- SATA II Transfer Rate of 3.0Gbps with Serial ATA 1.0 Specification
- USB 2.0 Specification with speed up to 480 Mbps
- Express Card/34 Form Factor Module
- supports WIN2000/XP/Vista/7
- incl. eSATA cable 0.3m
- incl. setup CD and user manual

111828



USB 2.0 PCMCIA Adapter

- connection of 2 USB components via USB A-jack to a notebook
- no external power required
- output current 500 mA per port
- compliant with EHCI, OHCI, 32-bit CardBus and PCMCIA Type II specifications
- supports Win98/ME/2000/XP/Vista/7, Mac OS 8.6 or above
- incl. driver software
- provides bus fault detection and over current protection

128145



FireWire IEEE 1394a PCMCIA Adapter

- 2 x IEEE-1394 external ports
- no external power supply needed
- 32bit cardbus
- chipset: VIA VT6306
- supports Win98/ME/2000/XP/Vista/7, Mac OS 8.6 or above

128144



USB 2.0 PCI Interface Card

- 4 x external Ports
- 1 x internal Port
- supports WIN2000/XP/Vista/7
- incl. setup CD

with VIA Chipset 128280

with NEC Chipset 128281



FireWire IEEE 1394a PCI Interface Card 3xext.

- overvoltage protection of all ports
- chipset: VIA
- supports WIN98/2000/ME/XP/Vista/7, Mac OS 9.x or above
- 3 x IEEE 1394a external Ports
- 1 x IEEE 1394a internal Port

128086

FireWire IEEE 1394a PCI Interface Card 3xext.

- incl. IEEE 1394a cable (6/4) M/M 1.5m
- incl. ULead 9.0 software

128085



USB 3.0 PCI Express Card 2-Port

- supports Low-speed (1.5Mbps) / Full-speed (12Mbps) / High-speed (480Mbps) / Super-speed (5Gbps) data rate
- supports USB legacy function
- compliant with PCI Express base Specification
- supports WIN XP/Vista/7

128284



USB 2.0-/FireWire IEEE 1394a PCI Interface Card

- 2 x IEEE 1394a external Ports
- 3 x USB2.0 external Ports
- 1 x USB2.0 internal Port
- Chipset: VIA
- supports WIN98/2000/ME/XP/Vista/7
- incl. IEEE 1394a Cable (6/4) S/S 1.5m
- incl. Setup-CD

128283



FireWire IEEE-1394a/b PCI Combo Card

- supports data transfer rates up to 800Mbps
- 2 x IEEE 1394b and 1 IEEE 1394a port external
- 4 pin internal power supply connector (cable included)
- Plug & Play, hot swap capability
- 32 / 64bit compatible
- incl. Y-power cable
- supports WIN98/2000/ME/XP/Vista/7, Mac OS 8.6 or above
- incl. manual and driver CD

128183



eSATA II PCI Combo Card 1+1

- 1 x shielded eSATA II port
- 1 x internal SATA port
- compliant to PCI specification 2x
- compliant to SATA 1.0a und SATA II specification
- Chipset: Initio 1620
- supports data transmission rates up to 150Mbps
- supports WIN98/2000/ME/XP/Vista
- incl. setup CD

111817



Converter SATA -> IDE Controller

- allows any types of SATA devices like Hard Disk Drive, CD/DVD Disc, CD/DVD ROM and Blu-Ray Disc, Blue-Ray ROM to work with IDE host controller
- compatible with Ultra ATA 133/100/66/33
- supports WIN 98SE/2000/ME/XP/Vista/7, Linux and Mac OS
- incl. Y-power cable
- incl. manual
- supports HDDs > 137GB

111831



SATA Mobile Rack

- SATA->SATA (3Gbps)
- supports SATA I & II
- supports 10000/15000rpm HDDs
- supports SATA RAID 0,1,5
- supports hot swapping
- supports HDDs up to 15000rpm
- safe and easy in/out sliding mechanism
- cableless point to point connection
- two power connector (15/4pin)
- ultra quiet turbo fan
- two LEDs
- plastic frame with dust protection flap

124938



eSATA II PCI Express Card 1+1

- 1x shielded eSATA II Port
- 1x internal SATA Port
- compliant PCI Express specification 1.0a
- Express Card data transfer rate up to 250 Mbps
- SATA II specification, data transfer rate up to 3.0Gbps
- supports RAID 0 and RAID 1
- supports WIN2000/ME/XP/Vista/7
- incl. setup-CD

111819



Converter IDE -> SATA Controller

- allows the operation of IDE devices e.g. HDDs, DVD, DVD-RAM, MO, CD-ROM, CD-RW etc. to SATA - controller
- compatible with Ultra ATA 133/100/66/33
- supports WIN98/2000/ME/XP/Vista/7, MAC OS
- incl. Y-power cable
- incl. SATA connection cable
- incl. manual
- supports HDDs > 137GB

111813

Coming soon



SATAIII PCIe Card

- compliant to 5Gbps PCI Express 2.0
- fully compliant with Serial ATA specifications 2.6
- supports SATA III transfer rate up to 6.0Gbps; compatible with SATA II/I
- supports ATA and ATAPI commands
- hotplug
- supports WIN98/2000/ME/XP/Vista/7, Mac OS

111910



Linking Series

To Join and Connect

- HDMI, DisplayPort Cable/Adapter
- Audio/Video Cable
- USB Cable
- SATA, eSATA Cable
- VGA, DVI Cable
- Patch Cable



DVI to VGA Adapter

- DVI (12+5) Male to VGA (HDB15) Female
- insulation resistance: min 10 Mega-ohms
- contact resistance: max 2 ohms
- DVI (12+5p) black solder type, gold flash
- HDB15F blue solder type terminal, gold flash with nuts
- resolution up to 1280 x 1024

DVI -> VGA, M -> F

119945



HDMI Adapter

- HDMI F-plug to F-plug
- provides bridge connection for HDMI cables
- construction: black, molded, gold plated plug
- supports Full HD resolution up to 1920 x 1200 (WUXGA)

HDMI -> HDMI, F -> F

118902



DisplayPort - HDMI Adapter

- DisplayPort M-plug to HDMI F-plug adapter
- compliant with DisplayPort 1.1 specification for both 1.62Gbps and 2.7Gbps.
- supports high resolutions up to 1920 x 1200 and Full HD on 1080p
- gold-plated connectors and latches
- Plug & Play

DisplayPort -> HDMI, M -> F

133430



HDMI - DVI Adapter

- construction: black, molded, gold plated plug
- supports Full HD resolution up to 1920 x 1200 (WUXGA)

HDMI -> DVI (24+1) Adapter, M -> F

118998

HDMI -> DVI (24+1) Adapter, F -> M

118988



HDMI Adapter

- HDMI M-plug to F-plug, right angle
- provides easy access for connecting HDMI cable and interface
- construction: black, molded, gold plated, right angled
- supports Full HD resolution up to 1920 x 1200 (WUXGA)

HDMI -> HDMI, M -> F, right angle

118903



DisplayPort - DVI Adapter

- DisplayPort M-plug to DVI (24+5) F-plug adapter
- compliant with DisplayPort 1.1 specification for both 1.62Gbps and 2.7Gbps.
- supports high resolutions up to 1920 x 1200 and Full HD on 1080p
- Plug & Play

DisplayPort -> DVI, M -> F

133431



DVI Dual-Link Cable

- supports WQXGA resolutions up to 2560 x 1600
- gold-plated connectors for maximum reliability
- extra flexibility and protection with nylon braided jacket
- color: black

DVI -> DVI (24+1), M -> M

1.8m	118967
3.0m	118968
5.0m	118969



HDMI Cable

- supports High Speed HDMI cable
- bandwidth: 10.2Gbps / 340MHz
- resolution: 1920 x 1080
- aluminum hood with gold-plated connectors for maximum reliability
- extra flexibility and protection with nylon braided jacket

HDMI -> HDMI, M -> M

2.0m	119202
3.0m	119203
5.0m	119205



USB 2.0 Connection Cable

- A/M -> B/M
- double shielded
- gold-plated plugs
- color: black

1.8m	128215
3.0m	128217



DisplayPort Cable

- DisplayPort Interface, 20-pin with latches
- delivers high-bandwidth digital audio/video signals over 1080p
- supports the DPCP standard in addition to HDCP
- gold-plated connectors for maximum reliability
- color: black

DisplayPort -> DisplayPort, M -> M

2.0m	119232
3.0m	119233



HDMI-DVI Adapter Cable

- fully compatible with High Speed HDMI cable
- supports WUXGA resolutions up to 1920 x 1200
- gold-plated connectors for maximum reliability
- extra flexibility and protection with nylon braided jacket
- color: black

HDMI -> DVI (18+1), M -> M

2.0m	119222
3.0m	119223
5.0m	119225



USB 2.0 Connection Cable

- A/M -> Mini 5 pin/M
- double shielded
- gold-plated plugs
- color: black

1.8m	128223
3.0m	128225



USB 2.0 Extension cable

- A/M -> A/F
- double shielded
- gold-plated plugs
- color: black

1.8m 128780
3.0m 128781



eSATA Cable

- 2 x eSATA 7pin Male
- shielded

0.3m 111830
1.0m 111821
2.0m 111822



SATA - eSATA Adapter Cable with Slot Bracket

- SATA 7pin > eSATA 7pin M/M
- shielded with metal latch
- slot bracket

0.3m 1-Port 111825
0.3m 2-Port 111826



USB 2.0 Mainboard Link

- 2 x USB A/F -> 2 x 5p mainboard connector

128132



SATA - eSATA Adapter Cable

- 1 x SATA 7pin > 1 x eSATA 7pin M/M
- shielded

0.5m 111823
1.0m 111824



SATA Internal Connection Cable

- overvoltage protection of all ports
- 2 x int. SATA 7 pin plug
- incl. metal latch

0.5m 111800
1.0m 111801

downward facing angled plug

0.5m 111802
1.0m 111804



SATA Power Supply Cable

1 x 5.25" Connector > 1 x SATA 15-pin Connector 0.15m

112050

1 x 5.25" Connector > 1 x SATA 15-pin Connector angled 0.15m

112055

1 x 5.25" Connector > 1 x SATA 15-pin Connector and 5.25" Jack 0.15m/0.30m

112052



SATA Multi Lane + SAS Cable

- 4 x SATA 7pin > 1 x SAS 32pin
- Connector with metal clips

0.5m 111845

1.0m 111841



FireWire IEEE 1394a Cable

- M/M, black

6/6-pin

1.8m 128050

3.0m 128051

4.5m 128052

6/4-pin

1.8m 128060

3.0m 128061

4.5m 128062

4/4-pin

1.80m 128070

3.00m 128071

4.50m 128072



Power Cable Internal

1 x 5.25" M -> 2 x 5.25", F 0.2m

112030

1 x 5.25" M -> 1 x 3pin F 0.3m

112035



SATA Power and Data Cable Internal

- 1 x SATA 15pin + 7pin F > 1 x 5.25" M (0.15m) and 1 x SATA 7pin F (0.5m)
- SATA Power and Data Cable Internal

112054



DVI - VGA Adapter Cable

- single Link/DVI -> VGA analog
- construction: beige, molded
- supports 1600x1200/60Hz (UXGA) and Wide Screen 1920x1200/60Hz (WUXGA)

DVI-A (12+5) M -> HDB15 M 1.8m

118941

DVI-A (12+5) M -> HDB15 F Adapter

118945



Monitor Cable 3+7, HDB15

- 75 Ohm
- 3 x coax + 7 x copper wires
- double shielded
- full metal case
- cable color: black

1.8m	M/M	118860
3.0m	M/M	118861
5.0m	M/M	118862
10.0m	M/M	118864
15.0m	M/M	118865
20.0m	M/M	118866
30.0m	M/M	118867

1.8m	M/F	118850
3.0m	M/F	118851
5.0m	M/F	118852
10.0m	M/F	118854
15.0m	M/F	118855
20.0m	M/F	118856



Monitor/Mouse Cable

- 9-pins
- 1:1 pin-out

DB9

1.8m	M/F	118100
3.0m	M/F	118101
5.0m	M/F	118102



Monitor Cable HDB15

- foil shielded
- knurled screws
- 1:1 pin out

1.8m St./St.	118080
1.8m St./Bu.	118130



USB 3.0 Connection Cable

- double shielded
- gold-plated plugs
- color: black
- A/M -> B/M

1.8m	128232
3.0m	128233

• A/M -> Micro 10pin/M	
1.8m	128284



High Speed HDMI Cable with Ethernet

- HDMI -> HDMI, M -> M
- supports High Speed HDMI cable with Ethernet specification
- color: black

1.0m	119241
2.0m	119242
3.0m	119243



SATAIII Cable

- supports data transfer rate of 6Gbps, 3Gbps, 1.5Gbps
- 2 x int. SATA 7-pin plug
- incl. metal latch

0.5m	111900
1.0m	111901

downward facing angled plug

0.5m	111902
1.0m	111903



Vision Series

To Extend and Sprawl

- HDMI Switch
- KVM Switch
- VGA Splitter
- HDMI Splitter – *Coming Soon*



HDMI Switch

- multifunctional on switching: intelligent or mechanical
- supports resolution up to 1080p
- supports 250MHz/2.5Gbps per channel (7.5Gbps all channel) bandwidth
- Plug & Play
- supports 12bit per channel (36bit all channel) deep color
- HDCP pass-through
- supports uncompressed audio such as LPCM
- supports compressed audio such as DTS Digital, Dolby Digital (including DTS-HD and Dolby True HD)

332702 2-Port HDMI Switch

332703 3-Port HDMI Switch



Pocket KVM Switches PS/2

- high VGA resolution: 1920 x 1440 / 70Hz
- metal enclosure for better EMV shielding
- space-saving cabling on the rear
- lockable connectors - better halt and protection
- reduces qty. of needed connectors - VGA connector
- for keyboard and mouse
- hot plug & play
- auto scan - shows all connected PCs
- emulation of keyboard/mouse - trouble-free booting
- switching via hotkey or button
- operating system independent
- incl. 2 or 4x KVM cable sets
- (VGA M >2xPS/2 M 1.8m)

1 User -> 2 PCs 331212

1 User -> 4 PCs 331214



PS/2 Cable KVM Switch 2-Port

- built-in bonded cable designed 1.2m
- computer selection by hot key
- high resolution video, supports up to 2048 x 1536, DDC2B
- compatible with PC, MAC and SUN operating systems
- Plug & Play, no drivers and power adapter needed
- autoscan-modus guarantees error-free PC switching and booting

331217



Desktop KVM Switches

- control of 2 / 4 PCs from one PC (keyboard/mouse) via PS/2 or USB with KVM combo cable set (PS/2+USB)
- high VGA resolution: 2048 x 1536 / 85Hz
- metal enclosure for ideal EMC-shielding
- keyboard emulation at each PC for easy booting
- hot swap support
- switching via front button or hot key
- DDC, DDC2 support
- auto scan interval: 5-250 seconds
- supports Windows OS, Linux, Mac OS9/OSX, Sun Microsystems
- recommended cable sets: 331992(1.8m), 331993(3.0m), 331995(5.0m)

1 User -> 2 PCs 331502

1 User -> 4 PCs 331504



USB Cable KVM Switch 2-Port

- built-in bonded cable designed 1.2m
- computer selection through wired remote switch 1.8m
- high resolution video, supports up to 2048 x 1536, DDC2B
- compatible with PC, MAC and SUN operating systems
- Plug & Play, no drivers and power adapter needed
- keyboard/mouse signals transmit separately through individual USB port

331522



Pocket KVM Switches USB + Audio

- high resolution : 2048 x 1536 / 85Hz
- ultra compact case
- operation via pressing front buttons or entering hot-key commands
- auto scan - 10 - 60 sec.
- independent/-simultaneous audio & PC switching
- LEDs for viewing port status
- no power supply required
- supports Windows OS, Mac OS, Linux, Novell
- incl. 2 or 4x KVM cable sets (VGA M >VGA M + USB-A M 1.2m)
- incl. 2 or 4x Audio cable sets

1 User -> 2 PCs 331512

1 User -> 4 PCs 331514



Mini DisplayPort To VGA

- Mini DisplayPort 1.2 compliant with 5.4Gbps bandwidth
- integrated triple 10-bit, 162 MHz video DAC for analog VGA signal output
- RGB output with 0 to 700mV range
- supports up to 1080p, 1920 x 1200 reduced blanking video resolution
- automatic sink detection
- low power standby mode operation initiated based on sink detection status
- low power operation-active 400mW, standby mode 15mW

133432



Mini DisplayPort To DVI

- compliant with Mini DisplayPort 1.2
- compliant with DVI 1.1, the max. transfer rate up to 2.5Gbps per channel
- PC resolutions: VGA, SVGA, XGA, SXGA and UXGA
- HDTV resolutions: 480i, 576i, 480p, 576p, 1080i, 1080p
- integrated ESD Protection to 8KV contact on all high speed I/O pins

133433



Mini DisplayPort To HDMI

- compliant with Mini DisplayPort 1.2
- supports HDMI (Deep color), max. transfer rate up to 2.5Gbps per channel
- PC resolutions: VGA, AVGA, XGA, SXGA and UXGA
- HDTV resolutions: 480i, 576i, 480p, 576p, 1080i, 1080p
- integrated ESD Protection to 8KV contact on all high speed I/O pins
- powered from Mini DisplayPort source

133434



VGA Splitter

- supports VGA, SVGA, XGA and multisync monitors
- video bandwidth 450 MHz
- resolution 2048 x 1536
- cascadable
- metal case for better EMI shielding
- power supply included
- connector in: 1xHDB 15 Female
- connectors out: 2/4/8x HDB 15 Female
- supports Windows 98SE , 2000, ME, XP, Vista and Mac OS 8.6 or higher

2-Port 332542

4-Port 332544

8-Port 332548



Cable Set PS2 + USB

- suited for equip KVM-Switches 332502/04
- HDB15M->HDB15/2xMD6/USB-A-M

1.8m 331992

3.0m 331993

5.0m 331995



Cable-VGA-Splitter 2-Port

- supports SVGA, VGA, XGA and multisync monitors
- bandwidth 450 MHz
- resolution 2048 x 1536
- cascadable
- power supply via USB-Y-cable (0.40m)
- Plug & Play
- no driver needed
- input connections: 1 x HDB15 M 0,20m
- output connections: 2 x HDB15 F
- supports Windows 98SE, ME, 2000, XP, Vista and Mac OS

332521



www.equip-info.net

Digital Data Communications Group

Global Headquarters:

Digital Data Communications GmbH, Germany

Global Offices:

Germany, Taiwan, Australia, Belgium, Brasil, Colombia, Denmark, East Africa, Greece, India, Italy, Israel, Latino América, Middle East, North Africa, The Netherlands, Portugal, Slovenia, South Africa, Spain, Sweden

equip distributed by:



2010.05.31